



Tyvek.

DuPont™ Flashing Tape

BUILDING SCIENCE BULLETIN



DuPont™ Flashing Tape is easy to install with a forgiving initial tack.

DuPont™ Flashing Tape provides a cost-effective way to help protect jambs, heads, corners and deep sills for today's windows and buildings.

By helping to channel water effectively outside of the home, DuPont™ Flashing Tape helps protect against water damage that can occur when moisture becomes trapped within the wall system. Providing a durable seal at the window-wall interface, DuPont™ Flashing Tape integrates easily with the complete line of DuPont™ Tyvek® Building Envelope Systems.

DuPont™ Flashing Tape uses superior performance butyl based adhesive system and a thermally stable polyolefin top-sheet that will not deteriorate or stain after extended exposure to temperature up to 82°C. It adheres well to most common building materials, including DuPont™ Tyvek® Building Envelope wraps, while maintaining a forgiving initial tack, thereby allowing for repositioning with its lightweight release liner and at external temperatures as low as -4°C. DuPont™ Flashing Tape meets the requirements for the AAMA 711-13 material standard at the highest classification level.

Disclaimer

All technical information set out herein is provided free of charge and is based on technical data which DuPont believes to be reliable. It is intended for use by persons having skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use are outside of our control we make no warranties express or implied in relation thereto and therefore cannot accept any liability in connection with any use of this information. Nothing herein is to be taken as a licence to operate under, or a recommendation to infringe any patents.

DuPont Protection Solutions

Australia

New Zealand

Toll-free: 1800-252-997 Toll-free: 0800-65-8080

DuPont™ Flashing Tape Offering

Roll Sizes Width x Length	Recommended Applications
101mm x 22.9m	For flashing jambs and heads of standard integral flange residential windows.
152mm x 22.9m 228mm x 22.9m	For applications requiring better coverage on the head of the window (such as flashing onto rough-side OSB).
304mm x 22.9m	For enhanced protection of deep window sills and inside and outside corner-flashings often used in multi-family construction.

BENEFITS

- 100% butyl adhesive
- Can be installed at external temperatures as low as -4°C
- Excellent adhesive to most common building materials
- Meets the AAMA 711-13 material standard: Class A (no primer) and Level 3 Thermal Exposure
- 120 days UV exposure



DuPont™ Flashing Tape comes in convenient 101mm, 152mm, 228mm and 304mm x 22.9m roll features a split release liner to help with easier product installation.

For more information about DuPont™ Tyvek® Building Envelope Systems, please visit us at www.Construction.Tyvek.com